



# ORIENT

## Photo coupler

### Product Data Sheet

MPN: ORPC-827 series

Customer: \_\_\_\_\_

Date: \_\_\_\_\_

#### SHENZHEN ORIENT COMPONENTS CO., LTD

Block A 3rd Floor No.4 Building, Tian'an Cyber Park, Huangge Rd, LongGang Dist, Shenzhen, GD

TEL: 0755-29681816

FAX: 0755-29681200

[www.orient-opto.com](http://www.orient-opto.com)


**Preliminary**

This datasheet is a preliminary design specification, and the formal specifications are subject to the recognition letter with jointly signed


## 1. Features

- (1) Current conversion ratio (Min 50% Working condition  $I_F=5\text{mA}$ ,  $V_{CE}=5\text{V}$ )
- (2) Insulation Voltage = 5,000Vrms
- (3) Response Time = (tr: TYP. 4 $\mu\text{s}$ ; tf: TYP. 5 $\mu\text{s}$  at  $V_{CE}=2\text{V}$ ,  $I_C=2\text{mA}$ ,  $R_L=100\ \Omega$ )
- (4) ESD pass HBM 8000V/MM 2000V
- (5) ORPC-827: 2-channel type  
ORPC-827M: 2-channel type  
ORPC-827S: 2-channel type
- (6) In compliance with RoHS, REACH standards
- (7) MSL Class I
- (8) Safety approval

UL approved (No.E323844)  
VDE approved (No.40029733)  
CQC approved (No.CQC19001231254 )



Pin No. and Internal connection diagram



1,3. Anode  
2,4. Cathode

5,7. Emitter  
6,8. Collector

## 2. Instructions

- (1). ORPC-827 series optical coupler consists of two GaAs transmitting tubes and two NPN transistors
- (2). Pin pitch of ORPC-827 is 2.54mm

## 3. Application Range

- (1) Switching power supply
- (2) Ammeter
- (3) Computer
- (4) Instrumental application, measurement machine
- (5) Imbursement equipments, duplicating machine, automat
- (6) Family-use electric equipments, such as fans
- (7) Signal transforming systems

#### 4. Absolute Maximum Ratings (Ta=25°C)

Parameter		Symbol	Rated Value	Unit
Input	Forward Current	I <sub>F</sub>	60	mA
	Peak forward Current(1us pulse)	I <sub>FP</sub>	1	A
	Reverse Voltage	V <sub>R</sub>	6	V
	Consume Power	P	70	mW
Output	Collector and emitter Voltage	V <sub>CEO</sub>	80	V
	Emitter and collector Voltage	V <sub>ECO</sub>	7	
	Collector Current	I <sub>C</sub>	50	mA
	Consume Power	P <sub>C</sub>	150	mW
Total Consume Power		P <sub>tot</sub>	200	mW
*1 Insulation Voltage		V <sub>iso</sub>	5000	Vrms
Maximum transient isolation voltage (Insulating oil test)		V <sub>IOTM</sub>	8000	V <sub>peak</sub>
Maximum repetitive peak isolation voltage		V <sub>IORM</sub>	850	V <sub>peak</sub>
Operation Temperature		T <sub>opr</sub>	-55 to + 110	°C
Storage Temperature		T <sub>stg</sub>	-55 to + 125	
*2 Soldering Temperature		T <sub>sol</sub>	260	

\*1. AC Test, 1 minute, humidity = 40~60%

Isolation voltage shall be measured using the following method.

(1) Short between anode and cathode on the primary side and between collector and emitter on the secondary side.

(2) The isolation voltage tester with zero-cross circuit shall be used.

(3) The waveform of applied voltage shall be a sine wave.

\*2. soldering time is 10 seconds

## 5. Electrical optical characteristics at TA=25°C

Parameter		Symbol	Min	Typ.*	Max	Unit	Condition
Input	Forward Voltage	V <sub>F</sub>	---	1.2	1.4	V	I <sub>F</sub> =20mA
	Reverse Current	I <sub>R</sub>	---	---	5	μA	V <sub>R</sub> =5V
	Collector Capacitance	C <sub>t</sub>	---	30	250	pF	V=0, f=1KHz
Output	Collector to Emitter Current	I <sub>CEO</sub>	---	---	100	nA	V <sub>CE</sub> =20V, I <sub>F</sub> =0mA
	Collector and Emitter attenuation Voltage	BV <sub>CEO</sub>	80	---	---	V	I <sub>C</sub> =0.1mA I <sub>F</sub> =0mA
	Emitter and Collector attenuation Voltage	BV <sub>ECO</sub>	7	---	---	V	I <sub>E</sub> =0.1mA I <sub>F</sub> =0mA
Transforming Characteristics	*1Current conversion ratio	CTR	50	---	600	%	IF=5mA VCE=5V
	Collector Current	I <sub>C</sub>	2.5	---	30	mA	
	Collector and Emitter Saturation Voltage	V <sub>CE(sat)</sub>	---	0.1	0.2	V	I <sub>F</sub> =20mA I <sub>C</sub> = 1mA
	Insulation Impedance	R <sub>iso</sub>	5×10 <sup>10</sup>	1×10 <sup>12</sup>	---	Ω	DC500V 40~60%R.H.
	Capacitance	C <sub>f</sub>	---	0.6	1.0	pF	V=0, f=1MHz
	Transforming Frequency	f <sub>c</sub>	---	80	---	kHz	V <sub>CE</sub> =5V, I <sub>C</sub> =2mA R <sub>L</sub> =100Ω, -3dB
	Rise Time	t <sub>r</sub>	---	4	18	μs	V <sub>CE</sub> =2V, I <sub>C</sub> =2mA, R <sub>L</sub> =100Ω
	Fall Time	t <sub>f</sub>	---	3	18	μs	

\*1 Current Conversion Ratio = I<sub>C</sub> / I<sub>F</sub> × 100%



## 6. Rank table of current transfer ratio (CTR)

CTR Rank	Min (%)	Max (%)	Condition
NO BIN	50	600	IF=5mA, VCE=5V, Ta=25°C
BC	130	400	
CD	200	600	
CD1	300	500	

## 7. Order Information

### Part Number

**ORPC-827XT-U-W-Y-Z**

### Note

X = Lead form option (S, M or none)

T = CTR Rank (BC,CD,CD1 or none)

U = Tape and reel option ( TA,TA1 or none).

W = Lead frame option (C:copper)


Y = 'V' code for VDE safety (This options is not necessary).

Z = 'G' code for Halogen free .

\* VDE Code can be selected.

Option	Description	Packing quantity
None	Standard DIP-8	45 units per tube
M	Wide lead bend (0.4 inch spacing)	45 units per tube
S(TA)	Surface mount lead form (low profile) + TA tape & reel option	1000 units per reel
S(TA1)	Surface mount lead form (low profile) + TA1 tape & reel option	1000 units per reel

## 8. Naming Rule




1. Manufacturer : ORIENT.
2. Part Number : 827.
3. CTR Rand  .
4. Lead frame Code : 'F' means Iron, 'C' means Copper.
5. Year Code  : '1' means '2021' and so on.
6. Week Code   : 01 means the first week, 02 means the second week and so on.
7. Day Code : "A to G" means "Monday to Sunday"
8. VDE Code   (Optional)
9. HF Code   : Halogen Free .
10. Anode.


\* VDE Mark can be selected.

## 9. Outer Dimension ( Unit: mm)


### 1. ORPC-827




### 2. ORPC-827M



3. ORPC-827S




**10. RECOMMENDED FOOT PRINT PATTERNS (MOUNT PAD)**




Unit: mm

## 11. Taping Dimensions

(1) ORPC-827-TA



(2) ORPC-827-TA1



Description	Symbol	Dimension in mm(inch)
Tape wide	W	16±0.3(0.63)
Pitch of sprocket holes	P0	4±0.1(0.15)
Distance of compartment	F	7.5±0.1(0.295)
	P2	2±0.1(0.079)
Distance of compartment to compartment	P1	12±0.1(0.472)

Package Type	TA/TA1
Quantities(pcs)	1000

## 12. Package Dimension

### (1) package dimension


DIP Type

Packing Information	
Packing type	Tube
Qty per Tube	45pcs
Small box (Inner) Dimension	525*128*60mm
Large box (Outer) Dimension	545*290*335mm
The Amount per Inner Box	2,250pcs
The Amount per Outer Box	22,500pcs

SOP Type

Packing Information	
Packing type	Reel type
Tape Width	16mm
Qty per Reel	1,000pcs
Small box (inner) Dimension	345*345*58.5mm
Large box (Outer) Dimension	620x360x360mm
Max qty per small box	2,000pcs
Max qty per large box	20,000pcs

### (2)Packing Label Sample



#### Note:


1. Material Code :Product ID.
2. P/N :Contents with "Order Information" in the specification.
3. Lot No. :Product weeks.
4. D/C :Product data.
5. Quantity :Packaging quantity.

### 13. Temperature Profile Of Soldering

#### (1) IR Reflow soldering (JEDEC-STD-020 compliant)

One time soldering reflow is recommended within the condition of temperature and time profile shown below. Do not solder more than three times.


Profile item	Conditions
Preheat	
- Temperature Min (T Smin )	150°C
- Temperature Max (T Smax )	200°C
- Time (min to max) (ts)	90±30 sec
Soldering zone	
- Temperature (TL )	217°C
- Time (t L )	60 sec
Peak Temperature	260°C
Peak Temperature time	20 sec
Ramp-up rate	3°C / sec max.
Ramp-down rate from peak temperature	3~6°C / sec
Reflow times	≤3



## (2) Wave soldering (JEDEC22A111 compliant)

One time soldering is recommended within the condition of temperature.

Temperature	260+0/-5°C
Time	10 sec
Preheat temperature	5 to 140°C
Preheat time	30 to 80 sec



## (3) Hand soldering by soldering iron

Allow single lead soldering in every single process. One time soldering is recommended.

Temperature	380+0/-5°C
Time	3 sec max

## 14. Characteristics Curves

Fig.1 Forward current  
vs Ambient temperature




Fig.2 Collector Power Dissipation  
vs. Ambient temperature




Fig.3 Forward Current vs. Forward Voltage




Fig.4 Collector-emitter Saturation Voltage vs. Forward Current




fig.5 Collector Current vs. Non-Saturated Collector Emitter Voltage




fig.6 Collector Current vs. Non-Saturated Collector Emitter Voltage




Fig.7 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.8 Relative Current Transfer Ratio vs. Ambient Temperature




Fig.9 Forward Current vs. Current Transfer Ratio




Fig.10 Collector Dark Current vs. Ambient Temperature




Fig.11 Collector-emitter Saturation Voltage vs. Ambient Temperature




Fig.12 Switching Time vs. Load Resistance




Fig.13 Respinse Time vs.  
Ambient temperature





Fig.14 Switching Time Test Circuit  
& Waveforms



## 15. NOTES

1. Orient is continually improving the quality, reliability, function or design and Orient reserves the right to make changes without further notices.
2. The products shown in this publication are designed for the general use in electronic applications such as office automation equipment, communications devices, audio/visual equipment, electrical application and instrumentation.
3. For equipment/devices where high reliability or safety is required, such as space applications, nuclear power control equipment, medical equipment, etc, please contact our sales representatives.
4. When requiring a device for any “specific” application, please contact our sales in advice.
5. If there are any questions about the contents of this publication, please contact us at your convenience.
6. The contents described herein are subject to change without prior notice.
7. Immerge unit’s body in solder paste is not recommended.